

NGINE AND EQUIPMENT	STANDARD	OPTIONAL
IGINE MODEL	ISB '17, 200 HP / 2600RPM / 520 FT-LB, CUMMINS	ISB '17, 220 HP / 2600RPM / 520 FT-LB, CUMMINS
TOTAL MODEL	ISB 17, 200 III 7 2000ICINI7 320 I I IB, COMMING	ISB '17, 240 HP / 2600RPM / 560 FT-LB, CUMMINS
		ISB '17, 260 HP / 2600RPM / 660 FT-LB, CUMMINS
		L9N '18 250 HP @ 730 FT-LB
		L9N '18 260 HP @ 660 FT-LB
		L9N '18 300 HP @ 860 FT-LB
		L9 '17, 260 HP / 2200RPM / 720 FT-LB, CUMMINS
		L9 '17, 270 HP / 2200RPM / 800 FT-LB, CUMMINS
		L9 '17, 300 HP / 2200RPM / 860 LB-FT, CUMMINS
		L9 '17, 330 HP / 2200RPM / 1000 LB-FT, CUMMINS
		L9 '17, 350 HP / 2200RPM / 1000 FT-LB, CUMMINS
		L9 '17, 350 Hi HP / 2200RPM / 1150 FT-LB, CUMMINS
KHAUST (DIESEL)	LH VERTICAL SMA	RH HORIZONTAL SMA
KHAUST (GAS)		RH HOR CATALYST
1111001 (0.10)		LH VERTICAL CATALYST
EF TANK	RH FRAME MTD 5 GAL. CAPACITY	LH FRAME MTD 5 GAL. CAPACITY
21 1711 (IX	KITT KAME MITE J. GAL. CALACIT I	
		LH FRAME MTD 10 GAL. CAPACITY
		RH FRAME MTD 10 GAL. CAPACITY
		NO DEF TANK PROVIDED
R CLEANER	13" ONE STAGE	13" ONE STAGE WITH SAFETY ELEMENT
ADIATOR	1000 SQ. IN. 3 ROW HIGH CAPACITY, COPPER / BRASS	1000 SQ. IN. ALUMINUM
ADIATOR SHELL/HOOD BEZEL	NO RADIATOR GUARD	RADIATOR GUARD
AN & DRIVE	FAN CLUTCH, VISCOUS	2-SPEED FAN
OOLANT HOSES/PIPING	SILICONE HOSES WITH STEEL TUBING	
OOLANT	EXTENDED LIFE COOLANT	
NGINE BLOCK HEATER		PHILLIPS 120V 1000 WATT
EATER RECEPTICAL LOCATION	NO BLOCK HEATER RECEPT. PROVIDED	RECEPTACLE LOCATED AT CAB STEPS, RH SIDE
LATER RECEI HEAE LOCATION	NO BLOCK HEATER RECEI 1.1 ROVIDED	•
EADERIC AID CLOW DI LIC	NO ELECTRIC CTARTING AID PROVIDED	RECEPTACLE LOCATED AT CAB STEPS, LH SIDE
TARTING AID-GLOW PLUG	NO ELECTRIC STARTING AID PROVIDED	GRID HEATER
EATER-ENGINE OIL PAN	NO OIL PAN HEATER PROVIDED	ZERO-START,120V-150W, OIL PAN HEATER
NGINE IDLE SHUT DOWN	ENGINE IDLE SHUT DOWN ENABLED ( 5 MINUTES )	ENGINE IDLE SHUT DOWN DISABLED
RANSMISSION AND EQUIPMENT	STANDARD	OPTIONAL
RANSMISSION MODEL	ALLISON 3000 SERIES,6-SPEED	ALLISON 3500 SERIES,6-SPEED
RANSMISSION GEARING	6-SPEED	
RANSMISSION CONTROLS	ALLISON PUSHBUTTON CONTROLS	
OOLER-TRANSMISSION OIL	OIL TO WATER TYPE	REMOTE MOUNTED TOC
RANSMISSION LUBRICANT	TRANSYND SYNTHETIC AUTO TRANS FLUID	
RIVESHAFT-MAIN	DANA SPICER 1710HD HALF ROUND	
RANSMISSION SUPPORTS	NO TRANSMISSION SUPPORTS PROVIDED	TRANSMISSION REAR SUPPORT
O-TRANSMISSION MOUNTED	NO TRANSMISSION SOFFORTS FROVIDED  NO TRANSMISSION MOUNTED PTO PROVIDED	PTO PREP - 3000/3500 TRANSMISSION W/ REAR SUPPORT
O-TRAINSIMISSION MOUNTED	TAO TRAINSIVIISSION IVIOUNTED FTO FROVIDED	
		PTO - MUNCIE CS24-A1010-H3BX RH 3000/3500 TRANSMISSION, RH MOUNTED
RONT AXLE AND EQUIPMENT	STANDARD  RANGE STEED AND STEED AND STANDARD STANDARD	OPTIONAL STATE OF THE STATE OF
XLE MODEL	DANA 1202W STEER AXLE, 12000 LB CAPACITY	DANA E-1322-W, 13,200 LB CAPACITY
		DANA E-1462W STEER AXLE, 14600 LB CAPACITY
		MERITOR MFS-14 STEER AXLE, 14700 LB CAPASITY
		MERITOR MFS-16 STEER AXLE, 16000 LB CAPASITY
ONT SUSPENSION	5500 LB FLATLEAF 12,500 GROUND CAPACITY	6,000 LB FLAT LEAF, 13,200K GND CAP
		6500 LB FLATLEAF 14,500 GROUND CAPACITY
		7500 LB FLATLEAF 16,500 GROUND CAPACITY
IOCV ARCORDERS	DOUBLE ACTING SINGLE HEAVY DUTY	1500 ED LEATELAE 10,500 OROUND CAFACITI
OCK ABSORBERS	DOUBLE ACTING SINGLE - HEAVY DUTY	DUAL INTEGRAL DOWER OTEERING TAGG
WER STEERING	INTEGRAL POWER STEERING W/O ASSIST RAM TAS65	DUAL INTEGRAL POWER STEERING TAS65
		INTEGRAL POWER STEERING W/O ASSIST RAM TAS85
		DUAL INTEGRAL POWER STEERING TAS85
OWER STEERING RESERVOIR	2 QUART REMOTE MOUNTED	DUAL INTEGRAL POWER STEERING TAS85 FOUR QUART REMOTE MOUNTED

## **AUTOCAR ACMD®**



Autocar Expert MY 2019 Medium Duty 4X2 Class 8 Standard and Optional Specifications			
BRAKES-FOUNDATION, FRONT AXLE	MERITOR 16.5X5 QP	MERITOR 16.5X6 QP	
BRAKE DRUM-FRONT	CAST IRON		
BRAKE SLACK ADJUSTERS-FRONT AXLE	MERITOR AUTOMATIC		
FRONT HUBS	STEEL HUB PILOTED,285MM BOLT CIRCLE		
REAR AXLE AND EQUIPMENT	STANDARD	OPTIONAL	
AXLE MODEL	MERITOR RS24-160, SINGLE REDUCTION AXLE (6.14 : 1 RATIO)	DANA SPICER 21060S 21,000 LB CAPACITY (6.17 or 7.17 : 1 RATIO)	
		DANA SPICER S21 - 170E SINGLE SPEED 21,000 LBS (6.17 or 7.17 : 1 RATIO)	
		DANA SPICER 21065T TWO SPEED 21,000 LBS (6.14/8.42 or 7.17/9.77 : 1 RATIO)	
		DANA S23-170, SINGLE REDUCTION AXLE (6.14 or 7.17 : 1 RATIO)	
		DANA S23-190E SINGLE REDUCTION AXLE (6.14 or 7.17 : 1 RATIO) DANA SPICER 23082T TWO SPEED 23,000 LBS (6.17/8.40/739 or 5.43/840/739: 1 RATIO)	
		MERITOR RS26-185, SINGLE REDUCTION AXLE (6.14 : 1 RATIO)	
		DANA S30-190 WIDE TRACK AXLE, (30,000 LB CAPACITY) (6.14 or 7.17 : 1 RATIO)	
		DANA S30-190, (30,000 LB CAPACITY) (6.14 or 7.17: 1 RATIO)	
REAR SUSPENSION	HENDRICKSON HTS 23,000 LBS	HENDRICKSON HTS 21,000 LBS	
		HENDRICKSON HTS 26,000 LBS	
		HENDRICKSON HTS 31,000 LBS	
		HAS - 210 AIR RIDE SUSPENSION HAS - 230 AIR RIDE SUSPENSION	
		REYCO 102CC 31000 LB GROUND CAPACITY	
		HENDRICKSON PAX-EX 262, AIR RIDE, 26,000 LB CAPACITY	
SHOCK ABSORBERS	2 SHOCK ABSORBERS	FOR AIR SUSPENSION - INBOARD MOUNTED	
		FOR AIR SUSPENSION - OUTBOARD MOUNTED	
LDG.	A DO AGAINA WAY O	NO SHOCK ABSORBERS REAR SUSP. PROVIDED	
ABS BRAKES	ABS 4S/4M W/PLC MERITOR 16.5X5 QP	ABS 4S/4M W/PLC AND ATC MERITOR 16.5X6 QP	
BRAKE DRUMS	CAST IRON	WIERTON 10.5A0 QI	
BRAKE SLACK ADJUSTERS-REAR AXLE	ARVIN MERITOR AUTOMATIC-SINGLE AXLE		
REAR HUBS	IRON HUB, HP 10 STUD		
CHASSIS AND EQUIPMENT	STANDARD	OPTIONAL	
WHEELBASE	164 INCHES	132, 135, 136, 138, 141, 144, 147, 149 INCHES	
		151, 152, 155, 157, 158, 161, 167, 170, 171, 174, 178 INCHES	
		181, 184, 186, 190, 193, 196 INCHES 200, 203, 206, 209, 212, 215, 218, 220, 221, 222, 227, 234, 247 INCHES	
		RANGE BY REQUEST	
FRAME	10" X 3" X 3/8" 120KSI STRAIGHT RAIL SECTION - 2.13M RBM		
FRAME REINFORCEMENT INNER	NO INNER FRAME REINFORCEMENT PROVIDED	.25" LINER, STANDARD LENGTH	
FRAME FASTENERS	HUCK BOLTS	FASTENERS AVAILABLE BY REQUEST FOR BODY MOUNTING	
BUMPER	STANDARD DUTY BUMPER	HEAVY DUTY	
TOW DEVICE(S) AIR TANK-BRAKE	TWO TOW HOOKS INTEGRAL W/X-MEMBER STEEL TANKS FOR SINGLE AXLE		
AIR TANK MOUNTING	AS MANY TANKS IN RAIL AS POSSIBLE		
PNEUMATIC SYSTEM (RAPID FILL)	STANDARD CUMMINS WARCO 19 7 CEM COMPRESSOR	OPTIONAL	
AIR COMPRESSOR AIR SYSTEM DRAIN VALVE	CUMMINS WABCO 18.7 CFM COMPRESSOR PULL CORDS ALL TANKS	PULL CORDS WITH DV/2 WET TANK DRAIN	
AIR SISILM DRAIN VALVE	TOLL COMPONED TRIMED	PULL CORDS WITH DV/2 WET TANK DRAIN  PULL CORDS WITH HEATED DV/2 WET TANK DRAIN	
		CENTRAL DRAIN MANIFOLD WITH DV/2 WET TANK DRAIN	
		CENTRAL DRAIN MANIFOLD WITH HEATED DV/2 WET TANK DRAIN	
		DV/2 IN ALL TANKS (NON-HEATED)	
AIR LINES-MAIN, CHASSIS	SAE J844 NYLON TUBING		
FUEL SYSTEM	STANDARD	OPTIONAL	
FUEL TANK-LEFT	TEMP. FUEL TANK	50 GAL RECT STEEL TANK, LH MOUNTED	
		50 GAL ALUMINUM RECR TANK, LH MOUNTED	



	Autocar Expert MY 2019 Medium Duty 4X2 Class 8	Standard and Optional Specifications
	The second secon	75 GAL 26" DIA UNPAINTED ALUMINUM
		75 GAL 26" ROUND STEEL TANK
		100 GAL 26" DIA UNPAINTED ALUM
		100 GAL 26" DIA STEEL
		ALTERNATE FUEL ENGINE-NO LH TANK
		DELETE LHS FUEL TANK
JEL TANK-RIGHT	DELETE RHS FUEL TANK	50 GAL RECT STEEL TANK, RH MOUNTED
JEL TANK-KIOHT	DELETE KIIS FUEL TANK	
		50 GAL ALUMINUM RECT TANK, RH MOUNTED
		75 GAL 26" DIA UNPAINTED ALUMINUM
		75 GAL 26" DIA STEEL
		100 GAL 26" DIA UNPAINTED ALUM
		100 GAL 26" DIA STEEL
JEL FILTER ENGINE MOUNTED	SPIN-ON, ENGINE MOUNTED	NATURAL GAS FUEL CLEANER
UEL FILTER CHASSIS MOUNTED	FLEETGUARD FS SERIES F / W SEPARATOR, PROBE & DASH LIGHT	FLEETGUARD FS SERIES F / W HEATER, SEPARATOR, PROBE & DASH LIGHT
		NO ADDITIONAL FUEL FILTER PROVIDED
UEL LINES	SAE J844 NYLON TUBING	STAINLESS STEEL FOR CNG OR LNG
LTERNATE FUEL STORAGE	NO BOC MOUNTED ALT FUEL STORAGE	CNG 60 DGE BOC CABINET SYSTEM - 4 TANKS, FMM MOUNTED BELOW ON LH
		CNG 75 DGE BOC CABINET SYSTEM - 5 TANKS, FMM MOUNTED BELOW ON LH
		CNG 75 DGE BOC CABINET SYSTEM - 3 TANKS, FMM MOUNTED BELOW ON LH
		CNG 60 DGE BOX CABINET SYSTEM - 4 TANKS/ INTEG FMM-HI PRESS PORT
		CNG 60 DGE BOX CABINET SYSTEM - 4 TANKS/ INTEG FMM-LOW PRESS PORT
TRES AND WHEELS	STANDARD	OPTIONAL
IRE SIZE & LOAD RANGE - FRONT	11R22.5G	11R22.5H
THE SHEET OF ESTIMATION THOUSE	11(22.5)	12R22.5J
		12R22.5H
		275/70R22.5J
		315/80R22.5L
		315/80R22.5M
RONT WHEELS	22.5x8.25 STEEL HP, 6.18" INSET, 5HH	22.5x8.25" ALUMINUM HP, 5.79" INSET, ALCOA #883677 LV1 FINISH
		22.5X9.00" ALUMINUM HP, 6.02" INSET, ACCURIDE (WEIGHT REDUCTION)
		22.5x9.0" STEEL HP, 6.38" INSET, 5HH
		22.5X9.0 STEEL, HP, 5.25" INSET, 5HH, ACCURIDE #29039
		22.5X9.00" ALUMINUM HP, 5.96" INSET, ALCOA #89U64
EAR TIRES	11R22.5G	11R22.5H
		12R22.5H
		275/70R22.5J
		275/70R22.5H
		315/80R22.5L
		315/80R22.5M
		455/55R22.5M
EAR WHEELS	22.5X8.25 STEEL, HP, 5HH	22.5X8.25 ALUMINUM HP, ALCOA #883677 LV1 FINISH
EAR WHEELS	22.5A0.25 STELL, III , SHII	
		22.5X9.00" ALUMINUM HP, ACCURIDE (WEIGHT REDUCTION)
		22.5X9" ALUMINUM HP, 5.96" INSET, ALCOA #89U64
		22.5X9.0 STEEL, HP, 5HH
		22.5X14" ALUMINUM HP, ALCOA #840608 LV1 FINISH
LECTRICAL SYSTEM	STANDARD	OPTIONAL
LECTRICAL SYSTEM	12V, NEGATIVE GROUND	
LTERNATOR	DELCO REMY 12V 130AMP 22SI	DELCO REMY 36SI 12V 160 AMP
		DELCO REMY 160 AMP, 28SI PAD MTD W/REMOTE SENSE
		DELCO REMY 200 AMP, 28SI PAD MTD.
TARTER	DENSO 12V STARTER W/OCP	DELCO REMY 12V 39 MT W/OCP
ATTERIES	2 BATTERIES, 12V, 1500CCA	2 BATTERIES, 31 ECL, 12V, 1900CCA
	··/ · // · · · · · ·	2 BATTERIES, 31 ECL, 12V, 2000CCA
/INDSHIELD WIPERS	ELECTRIC INTERMITTENT WIPERS	2 2.1112.1120, 31 202, 12 1, 20000011
		ECCO RMS 917 WITH MOTION DETECTOR
BACKUP ALARM	ECCO SMART ALARM SA917	
		NO BACKUP ALARM PROVIDED

## AUTOCAR ACMD®

**PAINT** 

STANDARD



AUTOUAIT AUTID		An ISO 9001:2000 Certified Company
	Autocar Expert MY 2019 Medium Duty 4X2 Class 8 Stan	ndard and Optional Specifications
HORN	SINGLE ELECTRIC	
HORN-AIR	NO AIR HORN PROVIDED	TWIN MOUNTED UNDER CAB
LIGHTING	STANDARD	OPTIONAL
HEADLAMPS	RECTANGULAR SEALED BEAM	LED HEADLAMPS
LAMPS-RUNNING	NO DAYTIME RUNNING LIGHTS PROVIDED	DAYTIME
LAMPS-STOP-TAIL	NO TAIL OR BACK-UP LAMPS PROVIDED	DOT 4" INCANDESCENT TAIL (TURN/BRAKE/BACK-UP) LAMPS DOT 4" LED TAIL (TURN/BRAKE/BACK-UP) LAMPS
LAMPS-MARKER	AMBER LED ROOF MARKERS	CLEARANCE (ROOF CORNER) LAMPS WIRED TO BATTERY SHUT OFF
CAB AND EQUIPMENT	STANDARD	OPTIONAL
CAB SHELL	SINGLE LEFT HAND DRIVE CAB	DUAL DRIVE LH AND RH SIT SINGLE RIGHT HAND DRIVE CAB
CAB DOORS	STEEL DOORS W/DUAL POWER WINDOWS	
STEP-CAB ACCESS, CAB MOUNTED	DUAL SELF CLEANING CAB ENTRANCE STEPS	
CAB FLOOR	WEAR RESISTANT MAT WITH FOAM BACK	
CAB DASH	DARK GREY WRAP-AROUND, 2X OVERSIZED CUP HOLDERS	
OVERHEAD CONSOLE	2X STORAGE BINS, CENTER MOUNTED RADIO SLEEVE	
CAB MOUNTING	PROGRESSIVE RUBBER MOUNTS - FRONT COIL AND SHOCK ABS - REAR	
CAB TILT MECHANISM-C.O.E.	HYDRAULIC TILT WITH OUTO ENGAGE SAFETY LATCH	
MIRRORS-DUAL WEST COAST	MIRROR, BLACK, MOTORIZED/HTD POLYCARBONATE HOUSING W/SQUARE	
	MOTORIZED/HTD CONVEX MIRROR	MIRROR, CHROME, HTD, REMOTE, W / LWR HTD CONVEX
MIRRORS-AUXILIARY	NO CONVEX AUX. MIRRORS PROVIDED	LOW MOUNT 8" CONVEX MIRROR BLACK POLYCARBONATE HOUSING
DOWN VIEW MIRRORS	NO DOWN VIEW MIRRORS PROVIDED	SINGLE DOWN VIEW MIRROR, RH SIDE
		DUAL DOWN VIEW MIRRORS, ONE EACH SIDE
GRILLE	AUTOCAR GRILLE BLACK	CHROMED AUTOCAR GRILLE
		AUTOCAR GRILLE WITH REMOVABLE WINTERFRONT COVER
		AUTOCAR CHROME GRILLE WITH REMOVABLE WINTERFRONT COVER
CAB CLIMATE CONTROL SYSTEM	44,000 BTU FRESH AIR, HEATER AND AIR CONDITIONER, DIGITAL CLIMATE CONTROL	
STEERING COLUMN	ADJ. TILT AND TELESCOPIC STEERING COLUMN	DUAL ADJ. TILT AND TELESCOPIC STEERING COLUMNS
STEERING WHEEL	SINGLE DRIVE 16 INCH DIAMETER	SINGLE DRIVE 18 INCH DIAMETER
		DUAL DRIVE 16 INCH DIAMETER
		DUAL DRIVE 18 INCH DIAMETER
SEAT-DRIVER	STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE
		ISRI HT914 HIGH BACK, AIR RIDE W/ RH ARM REST AND LUMBAR
SEAT-PASSENGER	STANDARD MECHANICAL SUSPENSION SEAT WITH ADJ. DAMPENER	ISRI HT914 HIGH BACK, AIR RIDE
		ISRI HT914 HIGH BACK, AIR RIDE W/ LH ARM REST AND LUMBAR
ADDITIONAL SEAT - PASSENGER	NO THIRD MAN SEAT AND LAP BELT PROVIDED	THIRD MAN SEAT AND LAP BELT - CENTER MOUNTED
SEAT COVERING	BLACK CONDURA PLUS® CLOTH FABRIC	
SEAT BELT	THREE POINT RETRACTABLE	THREE POINT RETRACTABLE BRIGHT ORANGE COLOR
		3RD MAN SEAT AND LAP BELT -CENTER MOUNTED
SUN VISORS	LEFT AND RIGHT SIDE	
RADIO	RADIO PREP IN OVERHEAD CONSOLE	AM/FM / CD STEREO, ROOF MTD
		AM/FM/WB/MP3/CD/USB/BLUETOOTH
POWER PORT	12V AND DASH MOUNTED CIGAR LIGHTER	
ADDITIONAL ELEC. SWITCHES	NO ADDITIONAL ELEC. SWITCHES	2 DASH SWITCHES, WIRED TO POWER
LAMPS-CAB INTERIOR	LED DOME LAMPS	FLEX MAP
KEY & LOCK SETS-IGN/DOORS	2 ADDITIONAL KEYS PER TRUCK (4 TOTAL)	4 ADDITIONAL KEYS PER TRUCK (6 TOTAL)
		KEYED ALIKE FLEET SET #1 (23112213)
DRIVER MONITORING SYSTEM	NO DRIVER CAM WIRING PREP OVERHEAD CONSOLE	DRIVER CAM WIRING PREP OVERHEAD CONSOLE
CAMERAS	NO CAMERAS OR PREP PROVIDED	3RD EYE CAMERA PREP (CAB ONLY)
TRUCK ELECTRICAL CONTROL MODULE	NO ELECTRONIC CONTROL MODULE	DIAGNOSTIC AND INFORMATION DISPLAY
TIRE PRESSURE MONITORING SYSTEM	NO TIRE PRESSURE MONITORING SYSTEM	TIRE PRESSURE MONITORING SYSTEM
VEHICLE MONITORING SYSTEM	NO GEOTAB TRUCK MONITOR OR PREP	GEOTAB TRUCK MONITOR PREP
		GEOTAB TRUCK MONITOR

OPTIONAL



Autocar Expert MY 2019 Medium Duty 4X2 Class 8 Standard and Optional Specifications				
CAB PAINT TYPE	STANDARD WHITE	CAB FIRST COLOR OTHER THAN STD, NON METALLIC		
CHASSIS COLOR	BLACK P3036	CAB FIRST COLOR, METALLIC CHASSIS COLOR OTHER THAN STD SPECIFY		
BUMPER COLOR	BUMPER COLOR SAME AS CAB WHITE	PAINT SAME AS CAB, STEEL		
		BUMPER COLOR SAME AS CHASSIS		
DISC WHEEL OR RIM COLOR	STEEL, E-COAT WHITE / ALUM-UNPAINTED	CUSTOM COLOR - SPECIFY (PRICE PER WHEEL) STEEL, E-COAT GREY/ ALUM-UNPAINTED		
AXLE WHEELEND COLOR	SAME AS CHASSIS			
FUEL CABINET PAINT TYPE	NO CABINET PAINT COLOR	CABINET COLOR, METALLIC CABINET COLOR OTHER THAN STANDARD, NON METALLIC		
		STANDARD WHITE		
BASIC WARRANTIES (INDUSTRY BEST)	STANDARD	OPTIONAL		
CHASSIS WARRANTY	STANDARD WARRANTY	EXTENDED WARRANTY - 2 YEARS / 200K MILES		
		EXTENDED WARRANTY - 3 YEARS / 300K MILES EXTENDED WARRANTY - 4 YEARS / 350K MILES		
		EXTENDED WARRANTY - 5 YEARS / 400K MILES		
ENGINE WARRANTY	CUMMINS STANDARD WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 ISB HD1 4YRS/200K MILES EXT WARRANTY PP1 MATRIX #231131		
		2017 ISB HD1 5YRS/250K MILES EXT WARRANTY PP1 MATRIX #231131		
		2017 ISB HD1 5YRS/300K MILES EXT WARRANTY PP1 MATRIX #231131		
		2017 ISL HD1 3YRS/100K MILES EXT WARRANTY PP1 MATRIX #231156 2017 ISL HD1 3YRS/150K MILES EXT WARRANTY PP1 MATRIX #231156		
		2017 ISL HD1 4YRS/200K MILES EXT WARRANTY PP1 MATRIX #231156		
		2017 ISL HD1 5YRS/250K MILES EXT WARRANTY PP1 MATRIX #231156		
		2013 ISL HD1 5YRS/300K MILES EXT WARRANTY PP1 MATRIX #231156		
		2015 ISL-G GT1 5YRS/200K MILES EXT WARRANTY PP1 2015 ISL-G GT1 5YRS/150K MILES EXT WARRANTY PP1		
CUMMINS AFTERTREATMENT	NO EXTENDED AFTERTEATMENT WARRANTY (2 YRS -ISL, 3 YRS ISB)	2017 ISB AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231345		
		2017 ISB AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231345		
		2017 ISB AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231345		
		2017 ISL AT3 AFTERTREATMENT 3YRS/100K MILES EXT WARRANTY MATRIX #231445 2017 ISL AT3 AFTERTREATMENT 3YRS/150K MILES EXT WARRANTY MATRIX #231445		
		2017 ISL AT3 AFTERTREATMENT 4YRS/200K MILES EXT WARRANTY MATRIX #231445		
		2017 ISL AT3 AFTERTREATMENT 5YRS/250K MILES EXT WARRANTY MATRIX #231445		
		2017 ISL AT3 AFTERTREATMENT 5YRS/300K MILES EXT WARRANTY MATRIX #231445		
TRANSMISSION WARRANTY	ALLISON 3YR WARRANTY	ALLISON 5YR WARRANTY ALLISON 5YR EDGE WARRANTY		
VEHICLE RATINGS VEHICLE TARE WEIGHT, FRONT	STANDARD  9 104 lbc	OPTIONAL		
VEHICLE TARE WEIGHT, FRONT VEHICLE TARE WEIGHT, REAR	8,104 lbs. 3,847 lbs.			
GAWF	12000 LBS	13000 LBS		
		14000 LBS		
CAWD	22000 L DS	16000 LBS 21000 LBS		
GAWR	23000 LBS	26000 LBS		
		30000 LBS		
GVWR	35000 LBS	34000 LBS		
		35000 LBS		
		36000 LBS 37000 LBS		
		38000 LBS		
		39000 LBS		
		40000 LBS		
		43000 LBS 44000 LBS		
		44000 LBS 45000 LBS		
		46000 LBS		



## Autocar Expert MY 2019 Medium Duty 4X2 Class 8 Standard and Optional Specifications

CAB WARNING DEVICES

DAYTIME RUNNING LAMPS

CAB INSTRUMENTATION

APPLICATIONS CONCRETE PUMPER, ASPHALT DISTRIBUTOR, SWEEPER, ROAD PATCHER, REFUSE, CITY DELIVERY/BOX TRUCK, PAINT STRIPER, GEN UTILITY, GRINDER, ETC 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 16, 17, 18, 20 YARD

SPEEDOMETER PARK BRAKE TACHOMETER HIGH BEAM ENGINE OIL PRESSURE TURN SIGNAL COOLANT TEMPERATURE LOW FUEL TRANSMISSION OIL TEMPERATURE LOW AIR VOLTMETER SEAT BELT FUEL LEVEL DPF HOUR METER HEST DEF LEVEL AIR RESTRICTION INDICATOR PRIMARY (A) AIR PRESSURE FILTER WITH WATER IN FUEL INDICATOR SECONDARY (B) AIR PRESSURE ODOMETER TRIPMETER OPERATORS CONTROLS OPTIONAL EQUIPMENT PARK BRAKE PUSH/PULL FIRE EXTINGUISHER DRY TYPE ABC 5LB. CAP MTD. IN CAB HEADLAMPS TRIANGLE FLARE KIT IN CAB TURN SIGNAL COLUMN MOUNTED ADDITIONAL INSTRUMENTATION AUTO NEUTRAL BRAKE PEDAL ACCELERATOR PEDAL EXHAUST BRAKE TRANSMISSION GEAR SELLECTOR PUSH BUTTON METHANE DETECTION SYSTEM BATTERY SHUTOFF SWITCH WITH EMERGENCY JUMPER STUDS PTO CONTROL SWITCH